

Down-Draft Grossing Table UCS Electrically Height-Adjustable



TekEquipment™

Ph: 1300 368 138

www.tekequipment.com.au

info@tekequipment.com.au

TekMed NZ™

Ph: 0800 456 217

info@tekmed.co.nz

www.tekmed.co.nz

The down-draft grossing table is equipped with air down draft system. This specialized work table guarantees a laboratory environment free of pollutants while slicing and preparing histological slide preparations and is even well suited for small dissections. Airflow travels throughout the entire working area and is vacuumed out downwards, which provides optimal removal of unsanitary vapours. MAC (maximum allowable concentration) values for formalin are below target throughout the entire vacuum-affected area. The cutting table is to be connected to a side-mounted exhaust system provided by the customer.

The UCS-E-1500-D model includes the following features:

- Dual working place
- Workstations with a large surface area
- Height-adjustable from 750 to 1000 mm
- Sturdy, self-supporting undercarriage with adjustable legs
- Low overall height of the upper structure increases leg room
- Work surface includes a seamlessly welded basin measuring 400 x 400 x 200 mm
- Basin includes integrated air vacuum
- Basin can be mounted to the right or left side
- Very sturdy, perforated and insertable working plates
- Integrated sprinkler system with adjustable valve for bath sanitation located underneath the perforated working plates
- Formalin sink with sieve insert
- Mixing tap with detachable cold and hot water shower
- Exhaust duct left or right side

Technical Data:

Dimensions W/D/H:	1500 x 1000 x 750 / 1000 mm
Exhaust Air capacity:	Min. 1000 m ³ /h
Material:	Brushed stainless steel (Material No. 1.4301 – ANSI 304)
Perforated working area:	approx. 960 x 920 mm
Cold / Warm water connection:	½"
Waste water connection:	2"
Exhaust duct diameter:	250 mm
Type:	UCS-E-1500-D
Article No:	060.100.015

KUGEL medical GmbH & Co. KG
Hermann-Köhl-Str. 2A
DE - 93049 Regensburg / Germany

Phone +49/941/208648-0
Fax +49/941/208648-29
www.KUGEL-medical.de



KUGEL
medical
■ ■ ■ ■

Down-Draft Grossing Table UCS Electrically Height-Adjustable

Model UCS-E-1750-D:

Dimensions W/D/H:	1750 x 1000 x 750 / 1000 mm
Exhaust Air capacity:	1300 m ³ /h
Material:	Brushed stainless steel (Material No. 1.4301 – ANSI 304)
Perforated working area:	approx. 1210 x 920 mm
Cold / Warm water connection:	½"
Waste water connection:	2"
Exhaust duct diameter:	250 mm
Type:	UCS-E-1750-D
Article No:	060.100.025

Model UCS-E-2000-D:

Dimensions W/D/H:	2000 x 1000 x 750 / 1000 mm
Exhaust Air capacity:	1600 m ³ /h
Material:	Brushed stainless steel (Material No. 1.4301 – ANSI 304)
Perforated working area:	approx. 1460 x 920 mm
Cold / Warm water connection:	½"
Waste water connection:	2"
Exhaust duct diameter:	250 mm
Type:	UCS-E-2000-D
Article No:	060.100.035

Model UCS-E-2250-D:

Dimensions W/D/H:	2250 x 1000 x 750 / 1000 mm
Exhaust Air capacity:	1900 m ³ /h
Material:	Brushed stainless steel (Material No. 1.4301 – ANSI 304)
Perforated working area:	approx. 1700 x 920 mm
Cold / Warm water connection:	½"
Waste water connection:	2"
Exhaust duct diameter:	250 mm
Type:	UCS-E-2250-D
Article No:	060.100.050

Model UCS-E-2500-D:

Dimensions W/D/H:	2500 x 1000 x 750 / 1000 mm
Exhaust Air capacity:	2200 m ³ /h
Material:	Brushed stainless steel (Material No. 1.4301 – ANSI 304)
Perforated working area:	approx. 1960 x 920 mm
Cold / Warm water connection:	½"
Waste water connection:	2"
Exhaust duct diameter:	250 mm
Type:	UCS-E-2500-D
Article No:	060.100.055

KUGEL medical GmbH & Co. KG
Hermann-Köhl-Str. 2A
DE - 93049 Regensburg / Germany

Phone +49/941/208648-0
Fax +49/941/208648-29
www.KUGEL-medical.de



KUGEL
medical
■ ■ ■ ■