

# Mobile Recirculated Active Carbon Air System AK-ULS-1000-F



Suitable for down-draft grossing tables, consisting of:  
Solid stainless steel housing with 4 controllable and lockable wheels, access panel at the up front for easy access to all filters and the exhaust air fan and backside with exhaust air grid and filter fleece.

**Activated carbon filter with potassium permanganate impregnated, cylindrically form with galvanized steel housing:**

Max. work temperature:	+80 °C
Max. relative humidity:	70%
Max. air flow:	approx. 1000 m <sup>3</sup> /h
Level of noise:	approx. 55 db (A)

The filter cartridge can easily replaced through the access panel.

#### **Technical Data:**

#### **Exhaust air fan:**

Speed:	2120 1/min
Voltage:	230V / 50 Hz
Power input:	128 Watt / 0,55 Amp. incl. continuous speed controller incl. hour counter
Exhaust duct diameter:	DN 246
Dimensions W/D/H:	1200 x 520 x 630 mm
Type:	AK-ULS-1000-F
Article No.:	060.260.021

**KUGEL medical GmbH & Co. KG**  
Hermann-Köhl-Str. 2A  
DE - 93049 Regensburg/Germany

Phone +49/941/20 86 48-0  
Fax +49/941/20 86 48-29  
[www.KUGEL-medical.de](http://www.KUGEL-medical.de)

