

Lift and Transport Truck HTW 50/140 with Digital Scale



The lift and transport truck has a rugged, torsion-resistant frame structure, steel powder-coated (grey – RAL 7035) with smoothly running, integrated hydraulic unit for foot-actuated vertical adjustment for easy handling. 4 steerable solid rubber wheels, 2 of them lockable, 1 enabling locking as regards to the direction, d = 125 mm with special roller bearings, permanently lubricated and maintenance-free, which ensure an absolutely noiseless movement. A stainless steel roller track comprising 5 carrying rollers of corrosion-resistant material and plastic coating has been arranged on top of the truck. A holding device secures the body tray or coffin plate lying on it. The slide handle of the lift and transport truck can be removed. An anti-collision buffer is mounted to the front end. The low deadweight permits straightforward shunting and operation of the lift and transport truck. A special valve ensures even lowering at various loads. Ready for use digital scale with single-button operation for easy handling. Taring over the entire weighing range. Easy-to-read LCD display. Operation via 9 Volt block battery includes electronic rapid charger. Easy-care plastic housing, mounted on a stainless steel shelf.

Technical Data:

Dimensions lowest Position W/D/H:	2150 x 750 x 360 mm
Dimensions highest Position W/D/H:	2150 x 750 x 1710 mm
Carrying capacity:	max. 250 kg
Dead weight:	approx. 100 kg
Weighting range:	0-200 kg
Precision:	+/- 500 g
Material:	Steel
Colour:	Lightgrey RAL 7035 (powder coated)
Type:	HTW 50/140
Article No.:	050.060.010

Additional models see back page

KUGEL medical GmbH & Co. KG
Hermann-Köhl-Str. 2A
DE - 93049 Regensburg/Germany

Phone +49/941/20 86 48-0
Fax +49/941/20 86 48-29
www.KUGEL-medical.de



KUGEL
medical

Lift and Transport Truck HTW 51/140 with Digital Scale – Made of Stainless Steel

The lift- and transport truck has a rugged, torsion-resistant frame structure, completely made of stainless steel (Material no. 1.4301 – ANSI 304) with smoothly running, integrated hydraulic unit for foot-actuated vertical adjustment for easy handling. 4 steerable solid rubber wheels, 2 of them lockable, 1 enabling locking as regards to the direction, $d = 125$ mm with special roller bearings, permanently lubricated and maintenance-free, which ensure an absolutely noiseless movement. A stainless steel roller track comprising 5 carrying rollers of corrosion-resistant material and plastic coating has been arranged on top of the truck. A holding device secures the body tray or coffin plate lying on it. The slide handle of the lift and transport truck can be removed. An anti-collision buffer is mounted to the front end. Ready for use digital scale with single-button operation for easy handling. Tarring over the entire weighing range. Easy-to-read LCD display. Operation via 9 Volt block battery includes electronic rapid charger. Easy-care plastic housing, mounted on a stainless steel shelf.

Technical Data:

Dimensions lowest Position W/D/H:	2150 x 750 x 360 mm
Dimensions highest Position W/D/H:	2150 x 750 x 1710 mm
Carrying capacity:	max. 250 kg
Dead weight:	ca. 100 kg
Weighting range:	0 – 200 kg
Precision:	+/- 500 g
Material:	Stainless steel (Material No. 1.4301 – ANSI 304)
Type:	HTW 51/140
Article No.:	050.130.010

TekEquipment™

Ph: 1300 368 138

www.tekequipment.com.au

info@tekequipment.com.au

TekMed NZ™

Ph: 0800 456 217

info@tekmed.co.nz

www.tekmed.co.nz

KUGEL medical GmbH & Co. KG
Hermann-Köhl-Str. 2A
DE - 93049 Regensburg/Germany

Phone +49/941/20 86 48-0
Fax +49/941/20 86 48-29
www.KUGEL-medical.de



KUGEL
medical
■ ■ ■ ■