

# Monoblock Refrigerator System H 80 Wall Mounted



Connector-ready cooling unit, which is ready for immediate use. Mounted directly on the side of the morgue. The units have a sturdy housing with low-noise emittance, are fully thermal, and are equipped with an air-cooled compressor. The safety utilities are in accordance with EN (DIN) standards, VDE regulations and VBG guidelines. Also included is a high-capacity evaporator with automatic defrosting, an electrical temperature regulation and a digital temperature indicator with connection and protective plug.

Refrigerant: R404A

Ambient temperature +5 °C up to +45 °C

## **Technical data:**

Temperature range:	+10 °C to -5 °C
Voltage:	230 V / 1 Ph / 50 Hz
Refrigeration capacity 0 °C inside +40 °C outside:	721 Watt
Rated Input (when normally running):	600 Watt
Rated Input:	3,8 Amp
Peak current:	17 Amp
Max current:	4,5 Amp
Defrost:	Hot gas defrosting
Weight:	52 kg
<u>Compressor:</u>	
Type:	Hermetic
Normal power:	250 Watt
<u>Condenser:</u>	
Air flow:	600 m <sup>3</sup> /h
<u>Evaporator:</u>	
Air flow:	600 m <sup>3</sup> /h
Air throw:	4 m (Standard / is affected by many factors)
Dimensions W/D/H:	400 x 280 x 735 mm
Type:	H 80
Article No.:	040.120.010

**KUGEL medical GmbH & Co. KG**  
Hermann-Köhl-Str. 2A  
DE - 93049 Regensburg / Germany

Phone +49/941/208648-0  
Fax +49/941/208648-29  
[www.KUGEL-medical.de](http://www.KUGEL-medical.de)



**KUGEL**  
medical  
■ ■ ■ ■

# Monoblock Refrigerator System H 130

## Wall Mounted



Connector-ready cooling unit, which is ready for immediate use. Mounted directly on the side of the morgue. The units have a sturdy housing with low-noise emittance, are fully thermal, and equipped with an air-cooled compressor. The safety utilities are in accordance with EN (DIN) standards, VDE regulations and VBG guidelines. Also included is a high-capacity evaporator with automatic defrosting, an electrical temperature regulation and a digital temperature indicator with connection and protective plug.

Refrigerant: R404A

Ambient temperature +5 °C up to +45 °C

### Technical data:

Temperature range:	+10 °C to -5 °C
Voltage:	230 V / 1 Ph / 50 Hz
Refrigeration capacity 0 °C inside +40 °C outside:	1171 Watt
Rated Input (when normally running):	900 Watt
Rated Input:	5,3 Amp
Peak current:	32 Amp
Max current:	8,3 Amp
Defrost:	Hot gas defrosting
Weight:	56 kg
<u>Compressor:</u>	
Type:	Hermetic
Normal power:	560 Watt
<u>Condenser:</u>	
Air flow:	600 m <sup>3</sup> /h
<u>Evaporator:</u>	
Air flow:	600 m <sup>3</sup> /h
Air throw:	4 m (Standard / is affected by many factors)
Dimensions W/D/H:	400 x 280 x 735 mm
Type:	H 130
Article No.:	040.120.020

**KUGEL medical GmbH & Co. KG**  
Hermann-Köhl-Str. 2A  
DE - 93049 Regensburg / Germany

Phone +49/941/208648-0  
Fax +49/941/208648-29  
[www.KUGEL-medical.de](http://www.KUGEL-medical.de)



**KUGEL**  
medical  
■ ■ ■ ■

# Monoblock Refrigerator System H 180 Wall Mounted



Connector-ready cooling unit, which is ready for immediate use. Mounted directly on the side of the morgue. The units have a sturdy housing with low-noise emittance, are fully thermal, and equipped with an air-cooled compressor. The safety utilities are in accordance with EN (DIN) standards, VDE regulations and VBG guidelines. Also included is a high-capacity evaporator with automatic defrosting, an electrical temperature regulation and a digital temperature indicator with connection and protective plug.

Refrigerant: R404A

Ambient temperature +5 °C up to +45 °C

## **Technical data:**

Temperature range:	+10 °C to -5 °C
Voltage:	230 V / 1 Ph / 50 Hz
Refrigeration capacity 0 °C inside +40 °C outside:	1716 Watt
Rated Input (when normally running):	1100 Watt
Rated Input:	6,7 Amp
Peak current:	35 Amp
Max current:	12,4 Amp
Defrost:	Hot gas defrosting
Weight:	80 kg
<u>Compressor:</u>	
Type:	Hermetic
Normal power:	740 Watt
<u>Condenser:</u>	
Air flow:	1200 m <sup>3</sup> /h
<u>Evaporator:</u>	
Air flow:	1200 m <sup>3</sup> /h
Air throw:	4 m (Standard / is affected by many factors)
Dimensions W/D/H:	620 x 280 x 830 mm
Type:	H 180
Article No.:	040.120.032

**KUGEL medical GmbH & Co. KG**  
Hermann-Köhl-Str. 2A  
DE - 93049 Regensburg / Germany

Phone +49/941/208648-0  
Fax +49/941/208648-29  
[www.KUGEL-medical.de](http://www.KUGEL-medical.de)



**KUGEL**  
medical  
■ ■ ■ ■

# Monoblock Refrigerator System H 220 Wall Mounted



Connector-ready cooling unit, which is ready for immediate use. Mounted directly on the side of the morgue. The units have a sturdy housing with low-noise emittance, are fully thermal, and equipped with an air-cooled compressor. The safety utilities are in accordance with EN (DIN) standards, VDE regulations and VBG guidelines. Also included is a high-capacity evaporator with automatic defrosting, an electrical temperature regulation and a digital temperature indicator with connection and protective plug.

Refrigerant: R404A

Ambient temperature +5 °C up to +45 °C

## **Technical data:**

Temperature range:	+10 °C to -5 °C
Voltage:	400 V / 3 Ph / 50 Hz
Refrigeration capacity 0 °C inside +40 °C outside:	2032 Watt
Rated Input (when normally running):	1600 Watt
Rated Input:	4,7 Amp
Peak current:	23 Amp
Max current:	6,3 Amp
Defrost:	Hot gas defrosting
Weight:	80 kg
<u>Compressor:</u>	
Type:	Hermetic
Normal power:	900 Watt
<u>Condenser:</u>	
Air flow:	1200 m <sup>3</sup> /h
<u>Evaporator:</u>	
Air flow:	1200 m <sup>3</sup> /h
Air throw:	4 m (Standard / is affected by many factors)
Dimensions W/D/H:	620 x 280 x 830 mm
Type:	H 220
Article No.:	040.120.040

**KUGEL medical GmbH & Co. KG**  
Hermann-Köhl-Str. 2A  
DE - 93049 Regensburg / Germany

Phone +49/941/208648-0  
Fax +49/941/208648-29  
[www.KUGEL-medical.de](http://www.KUGEL-medical.de)



**KUGEL**  
medical  
■ ■ ■ ■

# Monoblock Refrigerator System H 320

## Wall mounted



Connector-ready cooling unit, which is ready for immediate use. Mounted directly on the side of the morgue. The units have a sturdy housing with low-noise emittance, are fully thermal, and equipped with an air-cooled compressor. The safety utilities are in accordance with EN (DIN) standards, VDE regulations and VBG guidelines. Also included is a high-capacity evaporator with automatic defrosting, an electrical temperature regulation, and a digital temperature indicator with connection and protective plug.

Refrigerant: R404A

Ambient temperature +5 °C up to +45 °C

### Technical data:

Temperature range:	+10 °C to -5 °C
Voltage:	400 V / 3 Ph / 50 Hz
Refrigeration capacity 0 °C inside +40 °C outside:	2964 Watt
Rated Input (when normally running):	1800 Watt
Rated Input:	4 Amp
Peak current:	19 Amp
Max current:	7,1 Amp
Defrost:	Hot gas defrosting
Weight:	98 kg
<u>Compressor:</u>	
Type:	Hermetic
Normal power:	1100 Watt
<u>Condenser:</u>	
Air flow:	1500 m <sup>3</sup> /h
<u>Evaporator:</u>	
Air flow:	1800 m <sup>3</sup> /h
Air throw:	10 m (Standard / is affected by many factors)
Dimensions W/D/H:	620 x 350 x 830 mm
Type:	H 320
Article No.:	040.120.050

**TekEquipment™**

Ph: 1300 368 138

[www.tekequipment.com.au](http://www.tekequipment.com.au)

[info@tekequipment.com.au](mailto:info@tekequipment.com.au)

**TekMed NZ™**

Ph: 0800 456 217

[info@tekmed.co.nz](mailto:info@tekmed.co.nz)

[www.tekmed.co.nz](http://www.tekmed.co.nz)

**KUGEL medical GmbH & Co. KG**  
Hermann-Köhl-Str. 2A  
DE - 93049 Regensburg / Germany

Phone +49/941/208648-0  
Fax +49/941/208648-29  
[www.KUGEL-medical.de](http://www.KUGEL-medical.de)



**KUGEL**  
*medical*  
■ ■ ■ ■